

★★  
STANDARD

## Drive PPH25

Power 25 kW



Ergonomically arranged control panel



Safe due to high quality electronic components



Manometer display for main and feed cycle

The 2-stage control ensures optimum cutting speeds for all applications. A simple and uncomplicated drive

with product features reduced to the essentials.

# System & Accessories



## Technical data

### Electric motor

|       |       |
|-------|-------|
| Power | 25 kW |
|-------|-------|

### Hydraulic

|                 |   |
|-----------------|---|
| Pressure stages | 2 |
|-----------------|---|

|                 |            |
|-----------------|------------|
| 2 feed circuits | Gear wheel |
|-----------------|------------|

|              |                |
|--------------|----------------|
| Main circuit | Dual gear pump |
|--------------|----------------|

### Power

|         |                     |
|---------|---------------------|
| Stage 1 | 45 l/min at 230 bar |
|---------|---------------------|

|         |                     |
|---------|---------------------|
| Stage 2 | 50 l/min at 200 bar |
|---------|---------------------|

### Electric

|         |           |
|---------|-----------|
| Voltage | 400/480 V |
|---------|-----------|

|           |          |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

|                                     |      |
|-------------------------------------|------|
| Current consumption (400 V / 50 Hz) | 42 A |
|-------------------------------------|------|

### Dimensions & Weight

|        |        |
|--------|--------|
| Length | 720 mm |
|--------|--------|

|       |        |
|-------|--------|
| Width | 475 mm |
|-------|--------|

|        |        |
|--------|--------|
| Height | 988 mm |
|--------|--------|

|        |        |
|--------|--------|
| Weight | 145 kg |
|--------|--------|

## System & Accessories

### Drive unit PPH25

|           |                                      |
|-----------|--------------------------------------|
| 10984200* | Drive unit PPH25 / 380–420 V / 50 Hz |
|-----------|--------------------------------------|

|        |                              |
|--------|------------------------------|
| 976206 | Hose package 5 pieces 8 m FD |
|--------|------------------------------|

|        |                                     |
|--------|-------------------------------------|
| 975672 | Hose package 2 pieces 8 m FF (feed) |
|--------|-------------------------------------|

### Accessories

|        |                        |
|--------|------------------------|
| 973074 | El.-plug CEE 63/5 pol. |
|--------|------------------------|

|        |                              |
|--------|------------------------------|
| 999578 | On/off valve for wire sawing |
|--------|------------------------------|

\* Different voltage and frequency types are available upon request.