



# Floor saw FSE808

Cutting depth up to 320 mm



The electric floor saw FSE808 has been specially developed for locations that are difficult to access and allows a quick change from left to right cutting. The floor saw operates emission-free and low vibration, making it particularly suitable for cutting work on and

in buildings. The saw also has a step-less cutting depth adjustment via a threaded spindle with cutting depth indication. The fold-up saw cover allows effortless over-cuts. For easy transport, the floor saw can be dismantled into several handy assemblies.

# **System & Accessories**

#### **Technical data**

Saw blade	
Max. cutting depth	320 mm
Max. saw blade Ø	800 mm
Saw blade speed	1 250 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

#### Drive

Drive / motor	Electric
Output	7.5 kW
Voltage / frequency	400 V / 50 Hz
Nominal current	14.1 A
Engine cooling	Air cooling
Feed	Manual
Blade drive	Via V-belt

### Design

Continuous cutting depth adjustment via spindle	
Adjustable cutting depth indicator	
Left / right cutting function	
Corner flush cutting function	
Height-adjustable and 90° rotating handles	

## Dimensions & Weight

900 mm
580 mm
850 mm
156 kg

#### **System & Accessories**

Floor saw FSE808	
11002800	Floor saw FSE808
11002123	Flush cut blade guard 800 mm