

Grinding wheels - Rough grinding wheels



PREMIUM LONGLIFE Z-MAX rough grinding wheels

for steel



Application

- + For surface and edge grinding and for welding in demanding applications on different steel grades

We recommend

- + 4 mm thickness for peripheral grinding
- + 7 mm thickness for rough grinding
- + Best results when used on powerful angle grinders

Advantage

- + High-performance rough grinding wheel with LONGLIFE technology for maximum lifetime
- + Combination of zirconia alumina and innovative bond system offers unprecedented abrasiveness
- + Comfort Start ensures a comfortable start when grinding and increases the level of working comfort

Form	Type number	Dimension	Specification	PU
	27	34353701	115 x 4 x 22,23	ZA 24 S- BFX
		34353683	115 x 7 x 22,23	ZA 24 S- BFX
		34353702	125 x 4 x 22,23	ZA 24 S- BFX
		34353684	125 x 7 x 22,23	ZA 24 S- BFX
		34353704	150 x 4 x 22,23	ZA 24 S- BFX
		34353686	150 x 7 x 22,23	ZA 24 S- BFX
		34353705	178 x 4 x 22,23	ZA 24 S- BFX
		34353687	178 x 7 x 22,23	ZA 24 S- BFX
		34353706	230 x 4 x 22,23	ZA 24 S- BFX
		34353689	230 x 7 x 22,23	ZA 24 S- BFX