




Drill motors DME32MW | DME32UW

Core drilling up to Ø 350 mm



New, compact, robust and ergonomic design



Various drill rig attachments: Module Drill™ or universal plate



Performance and service indicator, levelling aid and drilling mode selection

The DME32 drill motor in the 3.2 kW power class combines excellent drilling performance with a compact design. The mechanical and electronic overload cut-out and the full metal housing guarantee high reliability. The built-in performance and service indicator and levelling aid also make it easy to control

the control panel. The 3-speed transmission together with additional speed control (on-drill and iron mode) ensure optimum drilling speed. The DME32 drill motor is available with the Modul Drill™ quick clamping system or universal plate drill rig attachments.



System & Accessories



Technical data

Drill motors	DME32MW		DME32UW	
	Voltage / Frequency	230 V / 50 Hz	110 V / 60 Hz	230 V / 50 Hz
Type no.	11005530	11005531	11005535	11005537
Drill diameter range	50–350 mm			
Nominal power	3.2 kW			
Nominal current	15 A	30 A	15 A	30 A
Load speed	230/460/720 rpm			
No load speed	420/820/1 250 rpm			
Motor cooling	Air			
Tool attachment	1 ¼"			
Operation	Rig-based			
Application	Wet			
3-speed transmission with oil pump	•			
Electric overload cut-out	•			
Mechanical overload cut-out	•			
PRCD protection switch	•		•	
Performance indicator	•			
Service indicator	•			
Drill and iron mode	•			
Drill rig attachment	ModulDrill™		Universal plate	

Dimensions & Weight

Length	540 mm			
Width	156 mm			
Height	184 mm	176 mm	184 mm	176 mm
Weight	13.1 kg	12.8 kg	13.1 kg	12.8 kg

System & Accessories

Core drilling system with drill rig DRA400	
11005530	Electric drill motor DME32MW
10987600	Drill rig DRA400
964906	ModulDrill™-Distance plate Ø +180 mm
11002077	Fastening bolt assembly

Accessories

378198	Extension 1 ¼" 100 mm
359471	Extension 1 ¼" 200 mm
359472	Extension 1 ¼" 300 mm
359473	Extension 1 ¼" 400 mm
359474	Extension 1 ¼" 500 mm
969138	Adapter 1 ¼" external – ½" internal
400439	Extension ½" 100 mm
359475	Extension ½" 200 mm
359476	Extension ½" 300 mm
889232	Extension ½" 400 mm
707230	Extension ½" 500 mm
10992646	Easy release element