

Flexible Abrasives - TFC Tyrolit Fast Change

★★★
PREMIUM

PREMIUM ZA-P45 V |
ZA-P45 P F TFC
 for universal use











Application




- + For coarse and fine grinding of steel, nonferrous metals, composites and gel coat

We recommend

- + Grit size 40 for grinding smaller welding seams and spot weld seams
- + Grit size 60 for maximum stock removal
- + Grit size 80/120 for a perfect surface finish

Advantage

- + Combination of zirconia alumina and a unique, strong paper backing for maximum abrasiveness and lifetime
- + Active coolant in the bond for cool and clean grinding
- + Tyrolit Fast Change system for quick and easy wheel changes thanks to velcro fastening

Form	Type number	Dimension	Grain	Max RPM	PU	
 	DISC-P	706136	115	60	12300	50 Pcs.
		706137	115	80	12300	50 Pcs.
		706138	115	120	12300	50 Pcs.
		706141	125	60	10500	50 Pcs.
		706142	125	80	10500	50 Pcs.
		706143	125	120	10500	50 Pcs.
		706144	150	60	8800	50 Pcs.
		706145	150	80	8800	50 Pcs.
		706146	150	120	8800	50 Pcs.
	DISC-V	706135	115	40	13300	50 Pcs.
		706139	125	40	12300	50 Pcs.